

EGO DUST



Opaque finish decorative paint with a sand effect, for interiors and exteriors.

Colour: White - Colour chart

Bases S.S.C.: P - ED

Packaging: 1 - 2.5 litres

Product characteristics

Composition: Based on acrylic resins in aqueous dispersion with inert balanced granulometry.

Mean specific weight: 0.950 kg/l.

Drying time: 3 - 8 hours as a function of the thickness applied.

Spreading rate: 6 - 8 sqm/litre/coat.

Film Aspect: Opaque.

Wet abrasion resistance: More than 5,000 Gardner cycles (ASTM 2486).

Resistance to External agents: Excellent (according to colours made of resistant to external agents pigments).

Storage: In tightly sealed cans, protected from frost.

Instructions for use

Use: To decorate or beautify properly prepared substrates.

Application method: Brush.

Dilution: Ready to use.

Application temperature range: 8 - 30 °C.

Cleaning of equipment: Clean with water immediately after use.

Systems of application

A) New / Old interiors plaster

- Surfaces must be dry and mature. Remove any dirt.
- Apply one brush coat of Isolante Acrilico, diluted 400% by volume with water.
- Apply two coats of Hydrowall Mat of the same finishing colour.
- Apply one brush coat of undiluted Ego Dust.

B) New / Old exteriors plaster

- Surfaces must be dry and mature. Remove any dirt.
- Apply one brush coat of white Ancoral PLS, diluted 40-60% by volume with Diluente sintetico 914090L.
- Wait at least 12 hours.
- Apply two coats of Hydrowall Mat in the finishing colour.
- Apply one brush coat of undiluted Ego Dust.

C) Wood, old or new:

- Sand thoroughly, removing any old coats of loose paint.
- Apply one brush coat of undiluted Opaco G9.
- After drying, provide a light sanding.
- Apply two coats of Hydrowall Mat in the finishing colour.
- Apply one brush coat of undiluted Ego Dust.

D) New iron

- Allow rust to form by wetting with water or by leaving it exposed outdoors for a few days in order to eliminate calamine.
- Sand thoroughly.
- Apply two brush coats of undiluted Metallite Bianca.
- Apply two coats of Hydrowall Mat in the finishing colour.
- Apply one brush coat of undiluted Ego Dust.

E) Old or existing iron

- Sand thoroughly, removing any old coats of loose paint.
- In the case of any exposed uncoated areas, touch up with undiluted Metallite Bianca.
- If the rust is widespread, apply one brush coat of undiluted Metallite Bianca to the entire surface.
- Sand lightly once the surface has dried.
- Apply two coats of Hydrowall Mat in the finishing colour
- Apply one brush coat of undiluted Ego Dust.

Warning: An uneven application of the product will highlight the final effect of it. For external applications it is recommended to verify the external agents resistance of pigments.

Product specification

Opaque finish decorative paint with a sand effect, for interiors and exteriors (such as Ego Dust); based on acrylic resin dispersed in water with inert balanced granulometry.

Mean specific weight: 0,950 – 1,050 kg/l.

Wet abrasion resistance: More than 5,000 Gardner cycles (ASTM 2486).

All technical information contained herein is indicative.
For more detailed information, please consult our TECHNICAL SERVICE DEPARTMENT.